

# SC SAFETY GATE

The BlueWater Self Closing Gate is tough, durable, economical, reliable and easy to install. Use it on ladders or in plant guardrail barriers.

The gate arm is dimensioned to provide maximum opening coverage. When the gate is installed with the top rail at OSHA's recommended nominal guardrail height of 42" above the work surface, the bottom rail of the gate is at OSHA's nominal mid-rail height of 21".

Installation is fast!! Our gate comes fully assembled and includes U-Bolts for standard installation. It requires only one 1/2" wrench and 5 minutes to install.

The gates come in 10 nominal sizes ranging from 18" to 48". Each gate size can be laterally adjusted up to 3-3/4" (-1-1/4" to +2-1/2") to ensure the gate fits properly in your opening for maximum safety.

You have a choice of a mild steel gate with either a Powder Coat Yellow or Hot Dipped Galvanized finish, or you can a Stainless Steel gate.



## KEY FEATURES

- ▶ Gate arm is dimensional to provide maximum opening coverage. The rails are spaced to match OSHA guardrail regulations.
- ▶ Our Universal Hinge Assembly fits various railing types up to 2" O.D. or flat surface mounting. Adapter kits are available for larger or uniquely shaped railings.
- ▶ Each gate is capable of swinging in either direction - simply invert the installation position.
- ▶ The self-closing feature employs two stainless steel torsion springs.
- ▶ 10 nominal sizes are available. And each is adjustable laterally up to 3-3/4".
- ▶ It's available in powder coat safety yellow, hot-dip galvanized, or stainless steel.

